

TYPE OF NOZZLE		W mm	PRESSURE (bar)								bar	
			0.7	2	4	6	1	2	4	7	1	4
			AIR (l/min)				STEAM (kg/h)				∠°	∠°
1/4 F - C5 - 1	1/4 M - C5 - 1	0.20	21	38	65	101	0.7	1.4	2.2	3.60	65	85
1/4 F - C5 - 2	1/4 M - C5 - 2	0.38	40	60	100	152	1.5	2.0	3.5	5.50	70	80
1/4 F - C5 - 3	1/4 M - C5 - 3	0.58	77	110	190	305	2.8	4.1	6.7	11.5	80	80
1/4 F - C5 - 4	1/4 M - C5 - 4	1.1	131	199	345	540	4.5	7.2	12.3	19.4	70	70
1/4 F - C5 - 5	1/4 M - C5 - 5	1.4	210	335	570	881	7.50	12.0	20.3	32.1	60	70
1/4 F - C5 - 6	1/4 M - C5 - 6	2.3	430	700	1150	1724	15.5	25.0	42.0	63.0	60	70
3/8 F - C5 - 1	3/8 M - C5 - 1	0.20	21	38	65	101	0.7	1.4	2.2	3.60	65	85
3/8 F - C5 - 2	3/8 M - C5 - 2	0.33	40	60	100	152	1.5	2.0	3.5	5.50	70	80
3/8 F - C5 - 3	3/8 M - C5 - 3	0.58	77	110	190	305	2.8	4.1	6.7	11.5	80	80
3/8 F - C5 - 4	3/8 M - C5 - 4	1.1	131	199	345	540	4.5	7.2	12.3	19.4	70	70
3/8 F - C5 - 5	3/8 M - C5 - 5	1.4	210	335	570	881	7.50	12.0	20.3	32.1	60	70
3/8 F - C5 - 6	3/8 M - C5 - 6	2,3	430	700	1150	1724	15.5	25.0	42.0	63.0	60	70