



Use high fluid pressure to produce a fine mist for dust suppression and evaporative cooling. Available in stainless steels or Brass, as a tip assembly, or as a single piece with 1/4" BSP thread. Flow rates 3.6 L/ hour to 320 L/ hour; operating pressure 2 Bar to 30 Bar.

- Humidifying and cooling
- Dust control
- Deodorizing
- Gas scrubbing

To order specify body style MX, tip CX, or tip assembly; capacity code and material

To order: specify thread size, model, capacity code or flow rate and operating pressure, material and whether the filter is required - e.g. 1/4 MX22 SS with filter.

If ordering the CX Tip specify whether the tip assembly body and retainer are required, and their material, too.

TYPE	Ø1 mm	PRESSURE (bar)						∠°
		2	5	10	15	20	30	
		CAPACITY (l/h)						
0.7	0.35	—	—	5.2	6.3	7.3	8.9	35°
1	0.4	—	—	6.4	7.8	9.1	11.2	60°
1.5	0.5	—	—	10.5	13.1	15.1	18.5	70°
2	0.6	—	10.2	14.3	17.7	20.1	25.2	75°
3	0.9	—	15.2	21.2	26.4	30.5	37.6	70°
4	1.1	—	20.1	29.1	35.2	40.4	50.5	80°
6	1.1	19.2	30.1	43	53	61	74	75°
8	1.5	26	40	57	70	81	99	90°
10	1.6	32	50	71	88	102	125	80°
12	1.9	38	61	86	105	120	150	80°
14	1.9	45	71	100	124	144	175	85°
18	1.9	57	91	129	158	182	220	85°
22	1.9	70	110	157	193	220	270	70°
26	2.2	83	131	186	225	260	320	85°