

Split Eyelet connectors consist of two formed clamps to fit around the tube, fastening bolts, a sealing gasket resistant to the more used chemical products and a connector body or boss. They provide a fast and economical way of installing nozzles and other screwed fittings in piping systems.

To order, specify sizes and material - e.g. Split eyelet connector, SS 1 1/2" x 1/4" BSP

TYPE	OUTLET CONNECTOR	Ø TUBES	Ø HOLE (mm)	DIMENSIONS	
				L	D
1/2 x 1/8	1/8 F				
1/2 x 1/4	1/4 F				
1/2 x 3/8	3/8 F	Ø 1/2"			
1/25 x 11/16	11/16 M	Ø 20 + 22 Ø	7	50	40
3/4 x 1/8	1/8 F				
3/4 x 1/4	1/4 F	3/4"			
3/4 x 3/8	3/8 F	Ø 25 + 27 Ø	7	50	46
3/4 x 11/16	11/16 M				
1 x 1/8	1/8 F				
1 x 1/4	1/4 F	1"			
1 x 3/8	3/8 F	Ø 30 + 35 Ø	7	60	46
1 x 1/2	11/16 M				
1 1/4 x 1/8	1/8 F				
1 1/4 x 1/4	1/4 F	1 1/4"			
1 1/4 x 3/8	3/8 F	Ø 40 + 45 Ø	17.5	72	61
1 1/4 x 1/2	1/2 F				
1 1/2 x 1/8	1/8 F				
1 1/2 x 1/4	1/4 F	1 1/2"			
1 1/2 x 3/8	3/8 F	Ø 45 + 51 Ø	17.5	86	67
1 1/2 x 1/2	1/2 F				
2 x 1/8	1/8 F				
2 x 1/4	1/4 F	2"			
2 x 3/8	3/8 F	Ø 54 + 60 Ø	17.5	96	75
2 x 1/2	1/2 F				