

TYPE	HP 0°		HP 15° - 25° 40° - 50° - 65°		Ø1 mm	PRESSURE (bar)								
	1/8	1/4	1/8	1/4		20	40	60	80	100	120	150	200	250
						CAPACITY (l/min)								
015	•	•	-	-	0.80	1.5	2.1	2.6	3.0	3.4	3.7	4.1	4.8	5.3
02	•	•	•	•	0.90	2.0	2.9	3.5	4.0	4.5	6.0	5.5	6.4	7.1
025	•	•	•	•	1.00	2.6	3.6	4.4	5.1	5.7	6.3	7.0	8.1	9.0
03	•	•	•	•	1.10	3.1	4.3	5.3	6.1	6.9	7.5	8.4	9.7	10.8
035	•	•	•	•	1.15	3.6	5.1	6.3	7.3	8.1	8.9	10.0	11.5	12.8
04	•	•	•	•	1.20	4.1	5.8	7.1	8.2	9.1	10.0	11.2	12.9	14.4
045	•	•	•	•	1.30	4.6	6.5	7.9	9.2	10.2	11.2	12.6	14.5	16.2
05	•	•	•	•	1.35	5.1	7.2	8.8	10.2	11.4	12.4	13.9	16.1	18.0
055	•	•	•	•	1.40	5.6	7.9	9.7	11.2	12.5	13.7	15.3	17.7	19.8
06	•	•	•	•	1.50	6.1	8.6	10.6	12.2	13.6	15.0	16.7	19.3	21.6
065	•	•	•	•	1.55	6.6	9.4	11.5	13.3	14.8	16.3	18.2	21.0	23.5
07	•	•	•	•	1.60	7.3	10.3	12.6	14.5	16.3	17.8	20.0	23.0	25.7
075	•	•	•	•	1.65	7.6	10.7	13.1	15.2	17.0	18.6	20.8	24.0	26.8
08	•	•	•	•	1.70	8.2	11.6	14.2	16.4	18.4	20.1	22.5	26.0	29.0
085	•	•	•	•	1.75	8.5	12.1	14.8	17.1	19.0	21.0	23.4	27.0	30.2
09	•	•	•	•	1.80	9.2	13.0	15.9	18.3	20.5	22.5	25.1	29.0	32.4
10	•	•	•	•	1.90	10.1	14.3	17.5	20.2	22.6	24.8	27.7	32.0	35.8
13	-	•	-	•	2.20	13.0	18.3	22.5	25.9	29.0	31.8	35.5	41.0	45.8
15	-	•	-	•	2.40	15.2	21.5	26.3	30.4	34.0	37.2	41.6	48.0	53.7
20	-	•	-	•	2.70	20.1	28.4	34.8	40.2	44.9	49.2	55.0	63.5	71.0
25	-	•	-	•	3.00	25.3	35.7	43.8	50.6	56.6	62.0	69.3	80.0	89.4
30	-	•	-	•	3.30	30.2	42.7	52.3	60.4	67.5	74.0	82.7	95.5	106.8
40	-	•	-	•	3.80	40.2	56.8	69.6	80.3	89.8	98.4	110.0	127	142.0
50	-	•	-	•	4.20	50.0	70.7	86.5	100	111.7	122.4	136.8	158	176.6
60	-	•	-	•	4.70	61.0	86.0	105	121	136	149	166.2	192	214.7